Modifying Kernel Boot Parameters

Kernel boot parameters configure how the SUSE Linux Enterprise Server for NVIDIA kernel starts and behaves, controlling areas such as hardware compatibility, performance and diagnostics. Set them temporarily from the GRUB 2 boot menu to test a change for a single boot. To apply a change to every subsequent boot, set it permanently in the boot loader configuration instead. Understanding the correct syntax and where to apply it lets you tune a system for a specific workload and resolve hardware-related boot problems. You can also roll back safely if a change causes issues.

Prerequisites

- To change kernel boot parameters on an experimental basis for the upcoming boot process, you need physical or remote console access to the system. Examples include a hypervisor console or a hardware management interface. This method does not work over SSH, since the system is not yet reachable over the network at that point in the boot process.

Publication Date: 12 Nov 2026

Contents

1 Introduction to kernel boot parameters 3

2 Difference between kernel boot parameters and linuxrc parameters 7

3 Temporarily modifying kernel boot parameters 8

4 Permanently modifying kernel boot parameters 9

5 Troubleshooting and FAQs 11

6 For more information 13

7 Legal Notice 13

A GNU Free Documentation License 14

1 Introduction to kernel boot parameters

Kernel boot parameters tell the kernel how to behave at startup. Knowing where they come from and how GRUB 2 passes them to the kernel makes it easier to change them correctly. This knowledge also helps you reason about which change to make for a given problem.

1.1 What are kernel boot parameters?

Kernel boot parameters are configurations passed to the kernel during the boot process managed by GRUB 2. The configurations are instructions to the GRUB 2 boot loader on how to configure certain features and make them behave in the intended manner. The method of modification depends on whether you want the change to affect only the next boot, or all subsequent boots.

1.2 Methods of modification

You can modify the kernel boot parameters using the following methods:

Temporarily

Changes are held in memory and apply only to the upcoming boot process. These changes made through the GRUB 2 boot menu are not written to any configuration file and are discarded after reboot.

Permanently

Changes are written to the `/etc/default/grub` file and persist across all subsequent boot processes. For permanent changes, we **recommend** using the **`update-bootloader`** command instead of directly editing the `/etc/default/grub` file.

However, if you directly edit the `/etc/default/grub` file, modify the `GRUB_CMDLINE_LINUX` or `GRUB_CMDLINE_LINUX_DEFAULT` variables. After modification, regenerate the GRUB 2 configuration by running the following command with administrative privileges.

```
> sudo grub2-mkconfig -o /boot/grub2/grub.cfg
```

This command applies only to the standard, non-immutable system. It fails on the immutable mode of SLE for NVIDIA, whose read-only root file system is only writable inside a new transactional snapshot. There, run **`update-bootloader`** through **`transactional-update`** instead of calling it directly:

```
> sudo transactional-update run update-bootloader --add-option PARAMETER=VALUE
```

To only regenerate the GRUB 2 configuration, without adding or removing a parameter, use the dedicated subcommand instead:

```
> sudo transactional-update grub.cfg
```

In immutable mode, changes take effect only after a reboot, since they live in a new snapshot until then.



Note: Snapshots do not stack without a reboot

Each **`transactional-update run`** call branches its new snapshot from the currently running system, not from an earlier snapshot you have not yet booted into. Running the command again before rebooting does not combine the two changes: only the most recent snapshot becomes the one that boots next, and it does not include the earlier, not-yet-activated change. Reboot to activate each change before making the next one.

1.3 Benefits of modifying kernel boot parameters

A few common reasons to modify kernel boot parameters:

- **Performance.** Tune the kernel for a specific workload. For example, the `quiet` parameter suppresses most boot messages, which shortens boot time.
- **Hardware compatibility.** Work around a hardware quirk the kernel misdetects by default. For example, the `acpi=off` parameter disables the Advanced Configuration and Power Interface (ACPI), which can resolve boot problems on older hardware.
- **Troubleshooting.** Isolate a driver or subsystem that is preventing the system from booting. For instance, the `nomodeset` parameter disables kernel mode setting, which helps when a graphics driver prevents the system from booting.

1.4 Examples of commonly modified kernel boot parameters

A few of the most commonly modified kernel boot parameters:

`root=`
: Specifies the path to the root file system.

`quiet`
: Suppresses most boot messages.

`splash`
: Displays a graphical boot splash screen.

`nomodeset`
: Disables kernel mode setting.

`debug`
: Enables debugging output.

`acpi=`
: Toggles the Advanced Configuration and Power Interface (ACPI) settings.

`selinux=0`
: Disables SELinux, which is enabled by default on SLE for NVIDIA 16. For the recommended approach, the `permissive` mode alternative, and how to relabel the file system after reenabling SELinux, see .

For a detailed understanding of all available kernel parameters and their possible values, source documentation is available at https://www.kernel.org/doc/Documentation/admin-guide/kernel-parameters.txt↗.

1.5 General rules for specifying values of kernel boot parameters

When modifying kernel boot parameters, follow these essential formatting rules:

Basic Parameter Spacing

Separate individual parameters with a single space:

- With **`update-bootloader`**, add each parameter with its own `--add-option` call. The command inserts the spacing for you:

```
> sudo update-bootloader --add-option quiet
> sudo update-bootloader --add-option splash
```

- In the `/etc/default/grub` configuration file for GRUB 2, use spaces between kernel parameters when passing them as string values to the `GRUB_CMDLINE_LINUX` or `GRUB_CMDLINE_LINUX_DEFAULT` variables.

- At the boot menu, press `E` to edit, locate the line starting with `linux`, and add parameters with spaces.

EXAMPLE 1: SEPARATE INDIVIDUAL PARAMETERS WITH A SINGLE SPACE

```
root=/dev/sda1 quiet splash
```

Parameter Value Assignment

When assigning values, use the equals sign (=) without spaces:

EXAMPLE 2: CORRECT METHOD OF ASSIGNING VALUES TO KERNEL PARAMETERS

```
root=/dev/sda1 video=1920x1080
```

EXAMPLE 3: INCORRECT METHOD OF ASSIGNING VALUES TO KERNEL PARAMETERS

```
root = /dev/sda1 video = 1920x1080
```

Values Containing Spaces

For values containing spaces, the handling differs between methods:

`update-bootloader`



Warning: Configuration corruption from unescaped spaces

`update-bootloader --add-option` does not quote or escape a value for you: a value containing a space is split into two separate boot parameters, corrupting the configuration. For a value containing spaces, edit `/etc/default/grub` directly or use the GRUB 2 boot menu instead, both described below.

GRUB 2 configuration file

Use either double quotes with escape characters, or use backslashes.

EXAMPLE 4: KERNEL PARAMETER VALUES CONTAINING SPACES IN THE GRUB 2 CONFIGURATION FILE

```
GRUB_CMDLINE_LINUX="root=\"/dev/mapper/USER VOLUME\""
```

```
GRUB_CMDLINE_LINUX="root=/dev/mapper/USER\ VOLUME"
```

GRUB 2 Boot Menu

Use only double quotes for values containing spaces:

EXAMPLE 5: KERNEL PARAMETER VALUES CONTAINING SPACES IN THE GRUB 2 BOOT MENU

```
root="/dev/mapper/USER VOLUME"
```

Multiple values for a kernel boot parameter

Use commas without spaces to separate multiple values for a single parameter in all methods:

EXAMPLE 6: MULTIPLE VALUES FOR A KERNEL BOOT PARAMETER

```
module_blacklist=nouveau,radeon
```

2 Difference between kernel boot parameters and linuxrc parameters

Older SUSE documentation distinguishes kernel boot parameters from `linuxrc` parameters. On SUSE Linux Enterprise Server for NVIDIA 16, that distinction no longer applies to an installed system: `linuxrc` is gone, and the parameters that used to be associated with it are ordinary kernel boot parameters handled by dracut.

2.1 What happened to linuxrc on SLE for NVIDIA 16?

`linuxrc` was the boot-time parameter parser used by the installer on earlier SLE for NVIDIA releases. It ran only during installation, before the target system's root file system existed, so it played no part in an already-installed system. It is not present on SLE for NVIDIA 16 at all: SLE for NVIDIA 16 installs exclusively with Agama, which does not use `linuxrc`. Agama provides a compatibility layer for a handful of `linuxrc` option names, for administrators migrating scripts or profiles built around the old parser. For the installer-time options and the compatibility mapping, see *Section 6, “For more information”*.

What remains is dracut, the framework that builds the initial RAM disk (initramfs). It brings up the environment the kernel needs before the real root file system is mounted, such as loading storage drivers or unlocking encrypted devices. Unlike `linuxrc`, dracut is not specific to installation. It also runs on every boot of an installed system.

The options that configure dracut are not a separate parameter category with their own syntax. They are ordinary kernel boot parameters, entered on the same GRUB 2 command line and following the same rules described in this article. Among these, dracut simply acts on the ones it recognizes before handing off to the rest of the boot process.

2.2 Examples of dracut parameters

The following kernel boot parameters are handled by dracut during the initrd stage, before the root file system is mounted:

- `rd.driver.blacklist=`: Specifies drivers to be blocked in the initrd. For example, `rd.driver.blacklist=nouveau` prevents the `nouveau` graphics driver from loading during the early stages of boot. This can be useful when troubleshooting driver-related boot issues.
- `rd.break`: Interrupts the boot process and drops the system to a shell within the initrd for debugging purposes. This parameter is helpful for diagnosing issues related to the early boot process, such as driver loading or file system mounting errors.
- `rd.retry=`: Specifies how long, in seconds, dracut retries configuring devices before giving up. For example, `rd.retry=240` extends the default 180-second timeout, which can help on hardware that takes longer than usual to initialize storage devices.
- `rd.luks=0`: Disables LUKS-encrypted device detection in the initrd. Detection is enabled by default on a system with an encrypted root file system. Use this parameter only if you need to turn it off, for example while troubleshooting an unrelated storage issue.

Because these are kernel boot parameters like any other, the temporary and permanent modification methods described elsewhere in this article apply to them. They work the same way as for `quiet` or `nomodeset`.

3 Temporarily modifying kernel boot parameters

To change kernel boot parameters on an experimental basis for the upcoming boot process, edit the options in the GRUB 2 boot menu. This method requires physical or remote console access to the system and does not work over an SSH connection. Such changes apply only to the upcoming boot process and the resulting session, and do not persist after reboot.

EXAMPLE 7: TEMPORARILY MODIFY KERNEL BOOT PARAMETERS USING THE GRUB 2 BOOT MENU

> As an example of modifying kernel boot parameters for the upcoming boot process, we disable the splash screen that you can see during the boot.
>
> 1. Restart the system. By default, the GRUB 2 menu appears with a brief countdown, and the saved entry boots automatically once it expires. If your system has been configured to hide the menu instead, press **Esc** while the SLE for NVIDIA boot logo shows to reveal it.

2. In the GRUB 2 boot menu, highlight the entry you want to modify using the arrow keys ↑ and ↓.
3. Press the E key. You are presented with an editor and the content of the selected boot entry. It looks similar to the following:

```
setparams 'SLE for NVIDIA 16.1'
...
...
echo 'Loading Linux KERNEL_VERSION ...'
linux /boot/vmlinuz-KERNEL_VERSION
root=UUID=56d052b3-9148-4161-8065-3d97378d5783 ${extra_cmdline} splash=silent
 resume=/dev/disk/by-uuid/69ff0e54-23a7-4ba8-8983-5a29c54ffa5e
quiet security=selinux selinux=1 crashkernel=377M,high crashkernel=72M,low
 mitigations=auto
```

4. Search for the string `splash=silent` and remove it.
5. To boot the entry, press F10 or Ctrl–X.
   To discard the changes and start anew, press the Esc key.

After executing the procedure and continuing with the boot process, no splash screen is observed for the current boot process. On the next boot, the splash screen reappears.

4 Permanently modifying kernel boot parameters

To change kernel boot parameters persistently for all subsequent boot processes, use the **`update-bootloader`** command as `root` or a user with equivalent administrative privileges.

UPDATE-BOOTLOADER OPTIONS USED IN THIS TASK

`--get-option` *PARAMETER*
: Prints the current value of a parameter, if set.

`--add-option` *PARAMETER=VALUE*
: Adds a parameter, or replaces its value if it is already set.

`--del-option` *PARAMETER*
: Removes a parameter.

`--config`
: Applies pending changes to the boot loader configuration.



Tip: Test before making a change permanent

On a production system, test the parameter temporarily first, as described in *Section 3, "Temporarily modifying kernel boot parameters"*. Confirm it has the effect you expect before committing to a change that applies to every subsequent boot.

EXAMPLE 8: PERMANENTLY MODIFY KERNEL BOOT PARAMETERS USING UPDATE-BOOTLOADER

As an example of modifying kernel boot parameters permanently, we disable the splash screen that appears during boot.



Warning

Before modifying kernel boot parameters, create a copy of the existing stable GRUB 2 configuration (`/etc/default/grub`) somewhere outside of your system. If the boot loader gets corrupted, or you face problems after booting, your system might fail to start. The backup lets you compare and restore the last known working configuration.

1. Log in as root, or switch to a user with equivalent administrative privileges.
2. Check whether the parameter you want to change is already set:

   ```
   # update-bootloader --get-option splash
   ```

   The command prints the currently configured value, for example `splash=silent`.
3. Remove the parameter from the default boot options:

   ```
   # update-bootloader --del-option splash
   ```

   To add or change a parameter instead of removing one, use **`update-bootloader --add-option`** *`PARAMETER=VALUE`*. Setting an already-present parameter again replaces its value rather than adding a duplicate entry.
4. Apply the change to the boot loader configuration:

   ```
   # update-bootloader --config
   ```
5. Reboot to confirm the splash screen no longer appears.

After executing the procedure and rebooting the system, we do not observe any splash screen for all subsequent boot processes.



Note: Editing the GRUB 2 configuration file directly

`update-bootloader` works consistently across the boot loaders SUSE supports, including GRUB 2 and the `systemd-boot` preview. If you prefer to edit `/etc/default/grub` directly instead, see *Section 1.2, "Methods of modification"* for the variables to modify and the command required to apply the change.

5 Troubleshooting and FAQs

A wrong or unsupported kernel boot parameter can leave a system unstable or unable to boot. This section covers how to identify a bad parameter, recover a system that no longer boots, and confirm stability after a change.

5.1 Troubleshooting modifications to kernel boot parameters

The following steps cover the most common issues: an incorrect parameter, a system that fails to boot, and a system that boots but behaves unpredictably afterward.

5.1.1 Identifying and correcting parameter issues

1. Validate parameter syntax and configuration:
    a. Verify the spelling accuracy of all kernel parameters.
    b. Check for correct formatting without unnecessary spaces.
    c. Confirm that the parameters are recognized by the kernel. If the parameter is already part of the standard configuration, check the current value with **`cat /proc/cmdline`**. For a complete list of allowed parameters, refer to the kernel documentation at https://www.kernel.org/doc/Documentation/admin-guide/kernel-parameters.txt.
2. Investigate system logs for detailed error information:

```
> sudo dmesg | grep -i error
```

```
> sudo journalctl -k -b
```

The **`journalctl -k -b`** output includes a `Command line:` entry showing the exact kernel boot parameters the kernel received for the current boot, which you can compare against what you intended to set.

3. Temporarily enable or disable suspicious parameters to isolate issues. For example, use `nomodeset` to troubleshoot device driver issues related to graphics cards.

5.1.2 Recovering from boot failures

A system that fails to boot is no longer reachable over the network. You need physical or remote console access (for example, a hypervisor console or a hardware management interface) to perform the following steps.

1. Boot into recovery mode:

    a. Restart the system.

    b. By default, the GRUB 2 menu appears automatically with a brief countdown. If your system has been configured to hide the menu instead, press `Esc` while the SLE for NVIDIA boot logo shows to reveal it.

    c. At the GRUB 2 menu, select *Advanced options for SLE for NVIDIA 16.1*.

    d. Select the `(recovery mode)` entry for the kernel version you want to boot.

    Recovery mode boots the system in single-user mode, without the parameters set for normal boot. It gives you a minimal working environment to fix the configuration.

2. Fix the configuration. Recovery mode does not use `GRUB_CMDLINE_LINUX_DEFAULT`, so you have a working root shell regardless of what it currently contains:

    - If you have a pre-modification backup, restore it:

    ```
    > sudo cp /etc/default/grub.bak /etc/default/grub
    ```

    - If you do not have a backup, remove the offending parameter directly:

    ```
    > sudo update-bootloader --del-option PARAMETER
    ```

3. Regenerate the GRUB 2 configuration:

    ```
    > sudo update-bootloader --config
    ```

5.1.3 Managing system stability

1. Before making further changes, back up the current, still-working configuration:

```
> sudo cp /etc/default/grub /etc/default/grub.bak
```

```
> sudo cp /boot/grub2/grub.cfg /boot/grub2/grub.cfg.bak
```

2. Check the system logs for errors or warnings introduced by the change:

```
> sudo journalctl -xe
```

```
> sudo dmesg | tail
```

   If a parameter change made the boot noticeably slower, check which units took the longest to start:

```
systemd-analyze blame
```

3. Remove the recently added parameters one at a time, rebooting after each, to find the cause.

4. If the issues persist, restore the backup from the first step, or boot from a previously working system snapshot.

6 For more information

- For a full list of kernel parameters and their possible values, see the https://www.kernel.org/doc/Documentation/admin-guide/kernel-parameters.txt upstream kernel documentation.
- For the boot options recognized by the Agama installer at install time, see . These replace the `linuxrc` parameters used by earlier SUSE installers.

7 Legal Notice

Copyright© 2006– 2026 SUSE LLC and contributors. All rights reserved.

Permission is granted to copy, distribute and/or modify this document under the terms of the GNU Free Documentation License, Version 1.2 or (at your option) version 1.3; with the Invariant Section being this copyright notice and license. A copy of the license version 1.2 is included in the section entitled “GNU Free Documentation License”.

For SUSE trademarks, see https://www.suse.com/company/legal/. All other third-party trademarks are the property of their respective owners. Trademark symbols (®, ™ etc.) denote trademarks of SUSE and its affiliates. Asterisks (*) denote third-party trademarks.

All information found in this book has been compiled with utmost attention to detail. However, this does not guarantee complete accuracy. Neither SUSE LLC, its affiliates, the authors, nor the translators shall be held liable for possible errors or the consequences thereof.

A GNU Free Documentation License

Copyright (C) 2000, 2001, 2002 Free Software Foundation, Inc. 51 Franklin St, Fifth Floor, Boston, MA 02110-1301 USA. Everyone is permitted to copy and distribute verbatim copies of this license document, but changing it is not allowed.

0. PREAMBLE

The purpose of this License is to make a manual, textbook, or other functional and useful document "free" in the sense of freedom: to assure everyone the effective freedom to copy and redistribute it, with or without modifying it, either commercially or non-commercially. Secondarily, this License preserves for the author and publisher a way to get credit for their work, while not being considered responsible for modifications made by others.

This License is a kind of "copyleft", which means that derivative works of the document must themselves be free in the same sense. It complements the GNU General Public License, which is a copyleft license designed for free software.

We have designed this License to use it for manuals for free software, because free software needs free documentation: a free program should come with manuals providing the same freedoms that the software does. But this License is not limited to software manuals; it can be used for any textual work, regardless of subject matter or whether it is published as a printed book. We recommend this License principally for works whose purpose is instruction or reference.

1. APPLICABILITY AND DEFINITIONS

This License applies to any manual or other work, in any medium, that contains a notice placed by the copyright holder saying it can be distributed under the terms of this License. Such a notice grants a world-wide, royalty-free license, unlimited in duration, to use that work under the conditions stated herein. The

"Document", below, refers to any such manual or work. Any member of the public is a licensee, and is addressed as "you". You accept the license if you copy, modify or distribute the work in a way requiring permission under copyright law.

A "Modified Version" of the Document means any work containing the Document or a portion of it, either copied verbatim, or with modifications and/or translated into another language.

A "Secondary Section" is a named appendix or a front-matter section of the Document that deals exclusively with the relationship of the publishers or authors of the Document to the Document's overall subject (or to related matters) and contains nothing that could fall directly within that overall subject. (Thus, if the Document is in part a textbook of mathematics, a Secondary Section may not explain any mathematics.) The relationship could be a matter of historical connection with the subject or with related matters, or of legal, commercial, philosophical, ethical or political position regarding them.

The "Invariant Sections" are certain Secondary Sections whose titles are designated, as being those of Invariant Sections, in the notice that says that the Document is released under this License. If a section does not fit the above definition of Secondary then it is not allowed to be designated as Invariant. The Document may contain zero Invariant Sections. If the Document does not identify any Invariant Sections then there are none.

The "Cover Texts" are certain short passages of text that are listed, as Front-Cover Texts or Back-Cover Texts, in the notice that says that the Document is released under this License. A Front-Cover Text may be at most 5 words, and a Back-Cover Text may be at most 25 words.

A "Transparent" copy of the Document means a machine-readable copy, represented in a format whose specification is available to the general public, that is suitable for revising the document straightforwardly with generic text editors or (for images composed of pixels) generic paint programs or (for drawings) some widely available drawing editor, and that is suitable for input to text formatters or for automatic translation to a variety of formats suitable for input to text formatters. A copy made in an otherwise Transparent file format whose markup, or absence of markup, has been arranged to thwart or discourage subsequent modification by readers is not Transparent. An image format is not Transparent if used for any substantial amount of text. A copy that is not "Transparent" is called "Opaque".

Examples of suitable formats for Transparent copies include plain ASCII without markup, Texinfo input format, LaTeX input format, SGML or XML using a publicly available DTD, and standard-conforming simple HTML, PostScript or PDF designed for human modification. Examples of transparent image formats include PNG, XCF and JPG. Opaque formats include proprietary formats that can be read and edited only by proprietary word processors, SGML or XML for which the DTD and/or processing tools are not generally available, and the machine-generated HTML, PostScript or PDF produced by some word processors for output purposes only.

The "Title Page" means, for a printed book, the title page itself, plus such following pages as are needed to hold, legibly, the material this License requires to appear in the title page. For works in formats which do not have any title page as such, "Title Page" means the text near the most prominent appearance of the work's title, preceding the beginning of the body of the text.

A section "Entitled XYZ" means a named subunit of the Document whose title either is precisely XYZ or contains XYZ in parentheses following text that translates XYZ in another language. (Here XYZ stands for a specific section name mentioned below, such as "Acknowledgements", "Dedications", "Endorsements", or "History".) To "Preserve the Title" of such a section when you modify the Document means that it remains a section "Entitled XYZ" according to this definition.

The Document may include Warranty Disclaimers next to the notice which states that this License applies to the Document. These Warranty Disclaimers are considered to be included by reference in this License, but only as regards disclaiming warranties: any other implication that these Warranty Disclaimers may have is void and has no effect on the meaning of this License.

2. VERBATIM COPYING

You may copy and distribute the Document in any medium, either commercially or non-commercially, provided that this License, the copyright notices, and the license notice saying this License applies to the Document are reproduced in all copies, and that you add no other conditions whatsoever to those of this License. You may not use technical measures to obstruct or control the reading or further copying of the copies you make or distribute. However, you may accept compensation in exchange for copies. If you distribute a large enough number of copies you must also follow the conditions in section 3.

You may also lend copies, under the same conditions stated above, and you may publicly display copies.

3. COPYING IN QUANTITY

If you publish printed copies (or copies in media that commonly have printed covers) of the Document, numbering more than 100, and the Document's license notice requires Cover Texts, you must enclose the copies in covers that carry, clearly and legibly, all these Cover Texts: Front-Cover Texts on the front cover, and Back-Cover Texts on the back cover. Both covers must also clearly and legibly identify you as the publisher of these copies. The front cover must present the full title with all words of the title equally prominent and visible. You may add other material on the covers in addition. Copying with changes limited to the covers, as long as they preserve the title of the Document and satisfy these conditions, can be treated as verbatim copying in other respects.

If the required texts for either cover are too voluminous to fit legibly, you should put the first ones listed (as many as fit reasonably) on the actual cover, and continue the rest onto adjacent pages.

If you publish or distribute Opaque copies of the Document numbering more than 100, you must either include a machine-readable Transparent copy along with each Opaque copy, or state in or with each Opaque copy a computer-network location from which the general network-using public has access to download using public-standard network protocols a complete Transparent copy of the Document, free of added material. If you use the latter option, you must take reasonably prudent steps, when you begin distribution of Opaque copies in quantity, to ensure that this Transparent copy will remain thus accessible at the stated location until at least one year after the last time you distribute an Opaque copy (directly or through your agents or retailers) of that edition to the public.

It is requested, but not required, that you contact the authors of the Document well before redistributing any large number of copies, to give them a chance to provide you with an updated version of the Document.

4. MODIFICATIONS

You may copy and distribute a Modified Version of the Document under the conditions of sections 2 and 3 above, provided that you release the Modified Version under precisely this License, with the Modified Version filling the role of the Document, thus licensing distribution and modification of the Modified Version to whoever possesses a copy of it. In addition, you must do these things in the Modified Version:

A. Use in the Title Page (and on the covers, if any) a title distinct from that of the Document, and from those of previous versions (which should, if there were any, be listed in the History section of the Document). You may use the same title as a previous version if the original publisher of that version gives permission.

B. List on the Title Page, as authors, one or more persons or entities responsible for authorship of the modifications in the Modified Version, together with at least five of the principal authors of the Document (all of its principal authors, if it has fewer than five), unless they release you from this requirement.

C. State on the Title page the name of the publisher of the Modified Version, as the publisher.

D. Preserve all the copyright notices of the Document.

E. Add an appropriate copyright notice for your modifications adjacent to the other copyright notices.

F. Include, immediately after the copyright notices, a license notice giving the public permission to use the Modified Version under the terms of this License, in the form shown in the Addendum below.

G. Preserve in that license notice the full lists of Invariant Sections and required Cover Texts given in the Document's license notice.

H. Include an unaltered copy of this License.

I. Preserve the section Entitled "History", Preserve its Title, and add to it an item stating at least the title, year, new authors, and publisher of the Modified Version as given on the Title Page. If there is no section Entitled "History" in the Document, create one stating the title, year, authors, and publisher of the Document as given on its Title Page, then add an item describing the Modified Version as stated in the previous sentence.

J. Preserve the network location, if any, given in the Document for public access to a Transparent copy of the Document, and likewise the network locations given in the Document for previous versions it was based on. These may be placed in the "History" section. You may omit a network location for a work that was published at least four years before the Document itself, or if the original publisher of the version it refers to gives permission.

K. For any section Entitled "Acknowledgements" or "Dedications", Preserve the Title of the section, and preserve in the section all the substance and tone of each of the contributor acknowledgements and/or dedications given therein.

L. Preserve all the Invariant Sections of the Document, unaltered in their text and in their titles. Section numbers or the equivalent are not considered part of the section titles.

M. Delete any section Entitled "Endorsements". Such a section may not be included in the Modified Version.

N. Do not retitle any existing section to be Entitled "Endorsements" or to conflict in title with any Invariant Section.

O. Preserve any Warranty Disclaimers.

If the Modified Version includes new front-matter sections or appendices that qualify as Secondary Sections and contain no material copied from the Document, you may at your option designate some or all of these sections as invariant. To do this, add their titles to the list of Invariant Sections in the Modified Version's license notice. These titles must be distinct from any other section titles.

You may add a section Entitled "Endorsements", provided it contains nothing but endorsements of your Modified Version by various parties--for example, statements of peer review or that the text has been approved by an organization as the authoritative definition of a standard.

You may add a passage of up to five words as a Front-Cover Text, and a passage of up to 25 words as a Back-Cover Text, to the end of the list of Cover Texts in the Modified Version. Only one passage of Front-Cover Text and one of Back-Cover Text may be added by (or through arrangements made by) any one entity. If the Document already includes a cover text for the same cover, previously added by you or by arrangement made by the same entity you are acting on behalf of, you may not add another; but you may replace the old one, on explicit permission from the previous publisher that added the old one.

The author(s) and publisher(s) of the Document do not by this License give permission to use their names for publicity for or to assert or imply endorsement of any Modified Version.

5. COMBINING DOCUMENTS

You may combine the Document with other documents released under this License, under the terms defined in section 4 above for modified versions, provided that you include in the combination all of the Invariant Sections of all of the original documents, unmodified, and list them all as Invariant Sections of your combined work in its license notice, and that you preserve all their Warranty Disclaimers.

The combined work need only contain one copy of this License, and multiple identical Invariant Sections may be replaced with a single copy. If there are multiple Invariant Sections with the same name but different contents, make the title of each such section unique by adding at the end of it, in parentheses, the name of the original author or publisher of that section if known, or else a unique number. Make the same adjustment to the section titles in the list of Invariant Sections in the license notice of the combined work.

In the combination, you must combine any sections Entitled "History" in the various original documents, forming one section Entitled "History"; likewise combine any sections Entitled "Acknowledgements", and any sections Entitled "Dedications". You must delete all sections Entitled "Endorsements".

6. COLLECTIONS OF DOCUMENTS

You may make a collection consisting of the Document and other documents released under this License, and replace the individual copies of this License in the various documents with a single copy that is included in the collection, provided that you follow the rules of this License for verbatim copying of each of the documents in all other respects.

You may extract a single document from such a collection, and distribute it individually under this License, provided you insert a copy of this License into the extracted document, and follow this License in all other respects regarding verbatim copying of that document.

7. AGGREGATION WITH INDEPENDENT WORKS

A compilation of the Document or its derivatives with other separate and independent documents or works, in or on a volume of a storage or distribution medium, is called an "aggregate" if the copyright resulting from the compilation is not used to limit the legal rights of the compilation's users beyond what the individual works permit. When the Document is included in an aggregate, this License does not apply to the other works in the aggregate which are not themselves derivative works of the Document.

If the Cover Text requirement of section 3 is applicable to these copies of the Document, then if the Document is less than one half of the entire aggregate, the Document's Cover Texts may be placed on covers that bracket the Document within the aggregate, or the electronic equivalent of covers if the Document is in electronic form. Otherwise they must appear on printed covers that bracket the whole aggregate.

8. TRANSLATION

Translation is considered a kind of modification, so you may distribute translations of the Document under the terms of section 4. Replacing Invariant Sections with translations requires special permission from their copyright holders, but you may include translations of some or all Invariant Sections in addition to the original versions of these Invariant Sections. You may include a translation of this License, and all the license notices in the Document, and any Warranty Disclaimers, provided that you also include the original English version of this License and the original versions of those notices and disclaimers. In case of a disagreement between the translation and the original version of this License or a notice or disclaimer, the original version will prevail.

If a section in the Document is Entitled "Acknowledgements", "Dedications", or "History", the requirement (section 4) to Preserve its Title (section 1) will typically require changing the actual title.

9. TERMINATION

You may not copy, modify, sublicense, or distribute the Document except as expressly provided for under this License. Any other attempt to copy, modify, sublicense or distribute the Document is void, and will automatically terminate your rights under this License. However, parties who have received copies, or rights, from you under this License will not have their licenses terminated so long as such parties remain in full compliance.

10. FUTURE REVISIONS OF THIS LICENSE

The Free Software Foundation may publish new, revised versions of the GNU Free Documentation License from time to time. Such new versions will be similar in spirit to the present version, but may differ in detail to address new problems or concerns. See https://www.gnu.org/copyleft/.

Each version of the License is given a distinguishing version number. If the Document specifies that a particular numbered version of this License "or any later version" applies to it, you have the option of following the terms and conditions either of that specified version or of any later version that has been published (not as a draft) by the Free Software Foundation. If the Document does not specify a version number of this License, you may choose any version ever published (not as a draft) by the Free Software Foundation.

ADDENDUM: How to use this License for your documents

```
Copyright (c) YEAR YOUR NAME.
Permission is granted to copy, distribute and/or modify this document
under the terms of the GNU Free Documentation License, Version 1.2
or any later version published by the Free Software Foundation;
with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts.
A copy of the license is included in the section entitled “GNU
Free Documentation License”.
```

If you have Invariant Sections, Front-Cover Texts and Back-Cover Texts, replace the “with...Texts.” line with this:

```
with the Invariant Sections being LIST THEIR TITLES, with the
Front-Cover Texts being LIST, and with the Back-Cover Texts being LIST.
```

If you have Invariant Sections without Cover Texts, or some other combination of the three, merge those two alternatives to suit the situation.

If your document contains nontrivial examples of program code, we recommend releasing these examples in parallel under your choice of free software license, such as the GNU General Public License, to permit their use in free software.